

MOTORISED AUTO DRAIN VALVE

Model - CMBV-A40



CONCEPT CMBV-A40 with many advanced features suitable for dusty, oily and extremely adverse conditions.

Model	Connection	MWP (Kg/cm ²)
CMBV-A16	1/2"	16
CMBV-A40	1/2"	40

Features :

- Valve body S.S. 304
- Suitable for mounting in open
- O-ring & Sealing of Teflon
- Auto close in case of power failure



Model - CMBV-A40

Technical specification:

Maximum Compressor Capacity	Any size (Recommended for 1500 cfm & above)
MWP	0-16 Kg/cm ² / 0-40 Kg/cm ²
Supply voltage options	115VAC, 230VAC, 24VDC, 50Hz (Depending on model)
Max. Fluid temperature	60°C
Time cycle range (ON/OFF)	6 Sec.-45 Sec.(ON), 4Min-48Hrs.(OFF). or 6 Sec.-15 Min.(ON), 3mm-24Hrs(OFF)
Actuator pcb	Microprocessor Based (User specific factory programmable)
Timer cycle indication	Bright LED illumination, LED program indicator
Test button	Yes
Valve type	2/2 way, Motorised ball valve
Valve orifice	12mm
Valve seals	FPM and Teflon
Inlet/Outlet connectons	1/2" (BSP) F, 1/2" NPT(F) optional
Serviceable	Yes
Interval & Drain time	Programmable **(As Per Below table)
Power connections	Cable & Plug (Optional) DIN 43650 A with Power Indication
Environmental protection	IP-65
Protection (Optional)	Input supply surge protection (For DIN43650)
Cable	1 Mtr. (Standard) or as per customer requirement

PROGRAMMING**			
Valve Open Time (ON)		Interval Time (OFF)	
CODE	Seconds	CODE	Minutes
A	6	0	4
B	7	1	8
C	9	2	16
D	12	3	32
E	15	4	64
F	18	5	128
H	22	6	256
L	30	7	720
U	35	8	1440
P	45	9	2880

OPTIONAL*		
Valve Open Code (ON)		Interval Time (OFF)
A	6 Sec.	3 Min.
B	9 Sec.	7 Min.
C	14 Sec.	14 Min.
D	19 Sec.	28 Min.
E	24 Sec.	1 Hrs.
F	30 Sec.	2 Hrs.
G	45 Sec.	4 Hrs.
H	1 Min.	8 Hrs.
P	5 Min.	16 Hrs.
L	15 Min.	24 Hrs.



CONCEPT TECHNOSTRUCTURES

Horizon Tower, 504, 5th Floor, J.L.N. Marg, Jaipur - 302017, India
 M. No.: +91- 8875009534, 9799917442
 Tel. No.+91- 0141-4981363
 Email : sales@conceptgroups.com / conceptsalesjpr@conceptgroups.com
 conceptjpr@conceptgroups.com
 Website : www.conceptgroups.com

Certificate Number:
 114629/A/0001/UK/En
 ISO 9001:2015

