

AUTOMATIC DRAIN VALVE

Model - EDV-16X



CONCEPT EDV-16X is Designed to Remove Condensate from Compressed Air Systems. Most Suitable for installation on Compressors After Coolers, Drip Legs, Moisture-separator etc. Valve has facility to Drain Manually on Power Failure.

Specifications :

Timer

- Interval Time : 1-128 Min. Adjustable
- Drain Time : 4 Sec. (Other on request)
- Supply Voltage : 230VAC (160-260), 50Hz (Other on request)
- Operating Temp. : 70°C (Maximum)
- Housing Material : High Impact Resistant ABS
- Connection : DIN 43650 A with Power Indication
- Indications : LED (Red)- Power On
LED (Yellow)- 'On' after every 15 sec. Indicate Healthiness of timer
LED (Green)- 'On' during drain cycle

Valve

- Type : 2 Way Direct Acting
- In/Out Ports : 1/4" / 1/2" / 3/4" / 1" BSP (F)
- Working Pressure : 16 Kg./cm²
- Valve Body : Bar Stock Aluminium with anodizing (Brass & S.S. On request)
- Orifice : 2.5 mm



Model - EDV-16X

Features - Fully Automatic - No Maintenance - Manual Test Switch - Indication for Valve Healthiness - Easy to Replace - 'O' Ring seal on Cycle Adjustment pots to Ensure Weather Proof Sealing - Small Compact Resistant ABS Timer

Automatic Drain Valve Model : EDV-16X

Model	Orifice	MWP	Connection Size	Features	Application	Remarks
EDV - 161	2.5 mm	16 Kg/cm ²	1/2" BSP (F)	Poppet Type, Compact, Test Switch, Fault Indication, Inbuilt Strainer	Small Receivers, Moisture separator, Drip Legs	Low cost, High Performance, Valve for Low Pressure applications.
EDV - 162	2.5 mm	16 Kg/cm ²	1" BSP (F)			
EDV - 163	2.5 mm	16 Kg/cm ²	3/4" BSP (F)			
EDV - 164	2.5 mm	16 Kg/cm ²	1/4" BSP (F)			



CONCEPT TECHNOSTRUCTURES

Horizon Tower, 504, 5th Floor, J.L.N. Marg, Jaipur - 302017, India
 M. No.: +91- 8875009534, 9799917442
 Tel. No.+91- 0141-4981363
 Email : sales@conceptgroups.com / conceptsalesjpr@conceptgroups.com
 conceptjpr@conceptgroups.com
 Website : www.conceptgroups.com

Certificate Number:
1146291A/0001/UK/En
ISO 9001:2015



CONCEPT
ADV - R-01