

AUTOMATIC DRAIN VALVE

Model - HDV-152



CONCEPT HDV-152 is Designed to Remove Condensate from Compressed Air Systems. Most Suitable for installation on Compressors After Coolers, Drip Legs, Moisture-separator etc. Valve has facility to Drain Manually on Power Failure.

Specifications :

Timer

- Interval Time : 1-128 Min. Adjustable
- Drain Time : 4 Sec.*
- Supply Voltage : 230VAC (160-260), 50Hz (Other on request)
- Operating Temp. : 70°C (Maximum)
- Housing Material : High Impact Resistant ABS
- Connection : DIN 43650 A with Power Indication
- Indications : LED (Red)- Power On
LED (Yellow)- 'On' after every 15 Sec. Indicate healthiness of timer
LED (Green)- 'On' during drain cycle
- Test Switch

Valve

- Type : 2 Way Pilot Operated
- In/Out Ports : 1" BSP (F)
- Working Pressure : 15 Kg./cm²
- Valve Body : Aluminium
- Orifice : 25 mm
- Pilot Pressure : Minium 2.5 Kg/cm²



Model - HDV-152

* Adjustable 4-15 Sec. is available on request.

Automatic Drain Valve Model : HDV-152

Model	Orifice	MWP	Connection Size	Features
HDV-152	25 mm	15 Kg/cm ²	1" BSP (F)	Poppet Type, Compact, Test Switch, Fault Indication, Inbuilt Strainer



CONCEPT TECHNOSTRUCTURES

Horizon Tower, 504, 5th Floor, J.L.N. Marg, Jaipur - 302017, India
M. No.: +91- 8875009534, 9799917442
Tel. No. +91- 0141-4981363
Email : sales@conceptgroups.com / conceptsalesjpr@conceptgroups.com
conceptjpr@conceptgroups.com
Website : www.conceptgroups.com

Certificate Number:
114629/A/0001/UK/En
ISO 9001:2015



CONCEPT
ADV - R-01

CATHDV15211241